



TECH BULLETIN

Toko Brand Management Office, Heber City, UT info@TokoUS.com 866-TOKO-USA

Application of HelX

HelX is the fastest Toko glide wax. More can be learned about HelX at this link: <http://www.tokous.com/Manuals/Helx%20Manual.pdf> Here are instructions on how to apply it:

Method 1

Best used when there is lots of time and a warm dry wax room.

1. Apply the base and HF wax layers of the day scraping and brushing between each layer.
2. Using the Dual Pad (which comes with the HelX), scrub the base with the yellow side which cleans the base on a microscopic level for the wax.
3. Liberally spray HelX on the base making sure that the entire base is completely wet.
4. Let the ski sit until the base is completely dry. This could take from 20-40 minutes depending on the room conditions.
5. Polish the HelX well with the white side of the dual pad.

Method 2

Best used when outside or in a hurry. This method requires more skill.

1. Apply the base and HF wax layers of the day scraping and brushing between each layer.
2. Using the Dual Pad (which comes with the HelX), scrub the base with the yellow side which prepares the base on a microscopic level for the wax.
3. Liberally spray HelX on the base making sure that the entire base is completely wet.
4. Using a roto cork at full rpms and corking “into” the ski base, cork the HelX until it is dry (and there is a waxy residue on the base).
5. Using a Nylon Polishing Brush, brush the HelX out of the structure of the base.
6. Polish the HelX well with the white side of the dual pad.

When done properly, either of these methods will yield the same result. The issue is how much time the waxer has and under what conditions the wax is being applied. If there is not enough time to allow the HelX to dry completely or if outdoors, then the best application method is using the rotocork.

